# GLORY

**GDB-100** Banknote deposit solution

A scalable banknote deposit automation device with advanced authentication and sorting features. GDB-100 facilitates large quantities of banknotes to be deposited by business and personal customers. Deposits are processed quickly and efficiently, eliminating long queues in the branch, reducing cash processing costs and also enabling cash inventory to be reused elsewhere in the branch.



## GDB-100 is quick and easy to integrate into the teller counter, self-service zone or within the back office.

| Processing unit   | Bulk note deposit module: Feed capacity 300 notes   |
|-------------------|---|
|                   | Note cassettes: Compact – 3 cassettes   |
|                   | High capacity – 5 cassettes   |
|                   | Note cassette capacity: 2500 notes*   |
|                   | ISM escrow capacity: max. 300 notes (option)  |
|                   | Cash reject capacity: max. 100 notes  |
|                   | Processing speed: 10 notes/second   |
|                   | Supported denominations: 128  |
|                   | Shutter for Input Pocket (option) and Reject Pocket (option)  |
|                   | ADA-compliance: Low safe model available  |
|                   | Front and rear cassette access (rear access – option)   |
|                   | Serial number recognition (SNR)** – optional  |
|                   | *Capacity dependent on condition of notes (2500 notes applies to 0.11mm per note under)                             |
| Human-machine     | Display: 15" colour LCD touch screen  |
| interface (HMI)   | Card reader: Motorised or DIP card reader (option)  |
|                   | Encrypting PIN Pad – PCI certified  |
|                   | Thermal receipt printer   |
| Security          | Physical: Electronic lock, secondary mechanical lock (option)   |
|                   | Standard: UL291-24 safe, with anchor bolt   |
|                   | Option: CEN III safe (available for 3-cassette variant only)  |
| Certifications    | Environmental certifications: ROHS, WEEE directive, EU battery directive<br>Safety compliance: UL, CE, CB, IEC60950 |
| Communication     | Standard LAN communication  |
| Communication     | XFS interfacing supported – REST interface  |
| Temperature and   | Operating: 5°C - 35°C, 20% - 80% RH   |
| relative humidity | Storage: -10°C - 60°C, 10% - 80% RH   |
|                   |   |

| Safe types  | High safe – Drop box for envelopes and other values                             |
|-------------|---|
|             | Low safe – ADA Compliant  |
|             | High volume version – 5 cassette  |
|             | Compact version – 3 cassette  |
| Dimensions  | Teller counter (low safe)   |
| (W × H × D) | 3 cassettes/Compact<br>550 × 930 × 840 mm                                       |
|             | 5 cassettes/high volume capacity<br>550 × 930 × 1117 mm                         |
|             | <b>Teller counter (high safe)</b><br>3 cassettes/Compact<br>550 × 1100 × 840 mm |
|             | 5 cassettes/high volume capacity<br>550 × 1100 × 1117 mm                        |
|             | Self Service Lobby (low safe)<br>3 cassettes/Compact<br>550 × 1406 × 840 mm     |
|             | 5 cassettes/high volume capacity<br>550 × 1406 × 1117 mm                        |
|             | Self Service Lobby (high safe)<br>3 cassettes/Compact<br>550 × 1576 × 840 mm    |
|             | 5 cassettes/high volume capacity<br>550 × 1576 × 1117 mm                        |

Images show 3-cassette variant. Specifications are subject to change without notice. Please read the instruction manual carefully to ensure correct equipment usage. All figures, capacities and speeds quoted in this brochure are as tested by GLORY LTD. They may vary depending on usage conditions and are not guaranteed.

\*\*Additional development maybe required for some currencies, please contact your local Glory office for further information.

# Related solutions...

# RBG-200 SERIES The RBG-200 series offers a unique and flexible design, allowing it to be configured to meet a wide range of banknote processing requirements. CASHINSIGHT™ ASSURE CashInsight Assure facilitates the operation of cash handling devices, providing immediate teller productivity. A configurable software platform for building secure and kiosk applications.

## Glory, Infinity View, 1 Hazelwood, Lime Tree Way, Chineham, Basingstoke, Hampshire RG24 8WZ, UK

### 🕿 +44 (0)1256 368000 🛛 info@uk.glory-global.com 🕀 glory-global.com

DS-GDB-100-0818\_4.0

Glory Global Solutions is part of GLORY LTD. This document is for general guidance only. As the Company's products and services are continually being developed it is important for customers to check that the information contained herein includes the latest particulars. Although every precaution has been taken in preparation of this document, the Company and the publisher accept no responsibility for errors or omissions. The Company and the publisher accept no liability for loss or damages resulting from the use of the information contained herein. This document is not part of a contract or licence save insofar as may be expressly agreed. All capabilities and capacity and throughput figures are subject to note/coin size, note/coin quality and process used. GLORY is a registered trademark of GLORY LTD. In Japan, the United States of America, and EU. All trademarks are owned by the GLORY LTD. In Japan, the United States of America and EU. All trademarks are owned by the GLORY LTD.